

## Listing of Claims

1. – 21. (Cancelled)

22. (Currently amended) A method for delivering a digital sound file to an electronic device, the method comprising:

dividing the digital sound file into first and second data files, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, and the second data file comprising the segments removed from each of a plurality of locations within the digital sound file;

encrypting at least a portion of the first data file using an encryption key;

communicating to the electronic device for persistent storage on the electronic device, a selected one of the ~~encrypted~~ first data file and the second data file; and

communicating to another electronic device for delivery to the electronic device, the unselected one of the first and second data files, the delivery to the electronic device from the other electronic device being through a selected one of a) a removable storage medium and b) a data stream via a communications network.

23. (Previously presented) The method of claim 22, wherein the digital sound file comprises a plurality of segments, and the dividing the digital sound file into first and second data files comprises:

removing a portion of the plurality of segments from the digital sound file;

storing the un-removed segments in the first data file; and

storing the removed segments in the second data file.

24. (Previously presented) The method of claim 23, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,

separation distance between two consecutive removed segments within the digital sound file, and

a portion of the encryption key.

25. (Previously presented) The method of claim 22, wherein the encryption key includes a key parameter that uses information from at least one of the removed segments.

26. – 29. (Cancelled)

30. (Currently amended) A method for processing a digital sound file with a computing device, comprising:

receiving and persistently storing by the computing device, a selected one of an ~~encrypted~~ first data file and a second data file, the first data file comprising the digital sound file having at least one segment removed from a ~~first~~ plurality of locations within the digital sound file, and the second data file comprising the at least one segments removed from a ~~second~~ the plurality of locations within the digital sound file, and at least a portion of the first data file having been encrypted;

receiving by the computing device, the unselected one of the first and second data files, via a selected one of a removable storage medium and a data stream;

decrypting the encrypted portion(s) of the first data file; and

combining the decrypted first data file and the second data file to form the digital sound file.

31. (Previously presented) The method of claim 30, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,

separation distance between two consecutive removed segments within the digital sound file, and

a portion of an encryption key for decrypting the encrypted first data file.

32. (Previously presented) The method of claim 31, wherein the first and second data files each include one or more segments, and combining the decrypted first data file and the second data file to form the digital sound file comprises:

using the data supplement to position the segments from the first and second data files into the digital sound file.

33.-34. (Cancelled)

35. (Currently amended) The method of claim 30, wherein decrypting the encrypted portion(s) of the first data file includes using a key, at least one parameter of the key is determined by the computing device from information in the second data file.

36. (Currently amended) An article of manufacture ~~computer program product~~ comprising a computer-readable medium containing computer program code for delivering a digital sound file to a computing device, the computer program code comprising instructions for:

dividing the digital sound file into first and second data files, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, and the second data file comprising the segments removed from each of a plurality of locations within the digital sound file;

encrypting at least a portion of the first data file using an encryption key;

communicating to the computing device for persistent storage on the computing device, a selected one of the ~~encrypted~~-first data file and the second data file; and

communicating to another computing device for delivery to the computing device, the unselected one of the first and second data files, the delivery being through a selected one of a) a removable storage medium and b) a stream of data.

37. (Currently amended) ~~The computer program product~~article of claim 36, wherein the digital sound file comprises a plurality of segments, and the dividing the digital sound file into first and second data files comprises:

removing a portion of the plurality of segments from the digital sound file;

storing the un-removed segments in the first data file; and

storing the removed segments in the second data file.

38. (Currently amended) ~~The computer program product~~article of claim 37, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,

separation distance between two consecutive removed segments within the digital sound file, and  
a portion of the encryption key.

39. (Currently amended) The ~~computer program product~~article of claim 36, wherein the encryption key includes a key parameter that uses information from at least one of the removed segments.

40.-43. (Cancelled)

44. (Currently amended) An article of manufacture ~~computer program product~~ comprising a computer-readable medium containing computer program code for a computing device to create a digital sound file, the computer program code comprising instructions for:

receiving and persistently storing by the computing device, a selected one of an ~~encrypted~~ first data file and a second data file, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, the second data file comprising the segments removed from each of a plurality of locations within the digital sound file, and at least a portion of the first data file having been encrypted;

receiving by the computing device, via a selected one of a) a removable storage medium and b) a data stream, the unselected one of the first and second data files;

decrypting the encrypted portion(s) of first data file; and

combining the decrypted first data file and the second data file to form the digital sound file.

45. (Currently amended) The ~~computer program product~~article of claim 44, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,

separation distance between two consecutive removed segments within the digital sound file; and

a portion of an encryption key for decrypting the encrypted first data file.

46. (Currently amended) The ~~computer program product~~article of claim 45, wherein the first and second data files each include one or more segments, and combining the first and second data files to form the digital sound file comprises:

the computing device using the data supplement to position the segments from the first and second data files into the digital sound file.

47.-48. (Cancelled)

49. (Currently amended) The ~~computer program product~~article of claim 44, wherein decrypting the encrypted first data file includes the computing device using a key, at least one parameter of the key determined from information in the second data file.

50. (Currently amended) The ~~computer program~~article of claim 44, further comprising instructions for rendering the combined digital sound file.

51. (Currently amended) The ~~computer program~~article of claim 44, further comprising instructions for storing on a non-persistent storage the received unselected one of the first and second data files.

52. (Currently amended) A method for delivering a digital sound file to a computing device, the method comprising:

dividing the digital sound file into first and second data files, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, and the second data file comprising the segments removed from each of a plurality of locations within the digital sound file;

encrypting at least a portion of the first data file using an encryption key;

storing on a removable storage device, for delivery to the computing device, a selected one of the ~~encrypted~~ first data file and the second data file; and

communicating to another computing device for streaming to the computing device, the unselected one of the first and second data files.

53. (Previously presented) The method of claim 52, wherein the digital sound file comprises a plurality of segments, and the dividing the digital sound file into first and second data files comprises:

- removing a portion of the plurality of segments from the digital sound file;
- storing the un-removed segments in the first data file; and
- storing the removed segments in the second data file.

54. (Previously presented) The method of claim 52, wherein the second data file includes a data supplement that indicates:

- location within the digital sound file of the removed segments,
- separation distance between two consecutive removed segments within the digital sound file, and
- a portion of the encryption key.

55. (Currently amended) A method for creating a digital sound file by a computing device, comprising:

- receiving by the computing device, from a removable storage medium, a selected one of ~~an encrypted~~ first data file and a second data file, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, ~~and~~ the second data file comprising the segments removed from each of a plurality of locations within the digital sound file, and at least a portion of the first data file having been encrypted;

- receiving by the computing device, a data stream comprising the unselected one of the first and second data files;

- decrypting the encrypted portion(s) of the first data file; and
- combining the decrypted first data file and the second data file to form the digital sound file.

56. (Previously presented) The method of claim 55, wherein the second data file includes a data supplement that indicates:

- location within the digital sound file of the removed segments,

separation distance between two consecutive removed segments within the digital sound file, and

a portion of an encryption key for decrypting the encrypted first data file.

57. (Previously presented) The method of claim 55, wherein the first and second data files each include one or more segments, and combining the decrypted first data file and the second data file to form the digital sound file comprises:

using the data supplement to position the segments from the first and second data files into the digital sound file.

58. (Currently amended) The method of claim 55, wherein decrypting the encrypted portion(s) of first data file includes using a key, at least one parameter of the key is determined by the computing device from information in the second data file.

59. (Previously presented) The method of claim 55 further comprising storing the selected and the unselected one of the first and second data files in persistent and non-persistent storage respectively.

60. (Currently amended) An article of manufacture ~~computer program product~~ comprising a computer-readable medium containing computer program code for delivering a digital sound file to a computing device, the computer program code comprising instructions for:

dividing the digital sound file into first and second data files, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, and the second data file comprising the segments removed from each of a plurality of locations within the digital sound file;

encrypting at least a portion of the first data file using an encryption key;

storing on a removable storage device for provision to the computing device, a selected one of the ~~encrypted~~ first data file and the second data file; and

communicating to another computing device for transmission via a data stream to the computing device, the unselected one of the first and second data files.

61. (Currently amended) The ~~computer program product~~article of claim 60, wherein the digital sound file comprises a plurality of segments, and the dividing the digital sound file into first and second data files comprises:

removing a portion of the plurality of segments from the digital sound file;  
storing the un-removed segments in the first data file; and  
storing the removed segments in the second data file.

62. (Currently amended) The ~~computer program product~~article of claim 61, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,  
separation distance between two consecutive removed segments within the digital sound file, and  
a portion of the encryption key.

63. (Currently amended) The ~~computer program product~~article of claim 60, wherein the encryption key includes a key parameter that uses information from at least one of the removed segments.

64. (Currently amended) An article of manufacture ~~computer program product~~ comprising a computer-readable medium containing computer program code for a computing device to create a digital sound file, the computer program code comprising instructions for:

receiving by the computing device, from a removable storage medium, a selected one of ~~an encrypted~~ first data file and a second data file, the first data file comprising the digital sound file having at least one segment removed from each of a plurality of locations within the digital sound file, the second data file comprising the segments removed from each of a plurality of locations within the digital sound file, and the first data file having at least a portion encrypted;

receiving with the computing device, a stream of video data comprising the unselected one of the first and second data files;

decrypting the encrypted portion(s) of the first data file; and



combining the decrypted first data file and the second data file to form the digital sound file.

65. (Currently amended) The ~~computer program product~~article of claim 64, wherein the second data file includes a data supplement that indicates:

location within the digital sound file of the removed segments,  
separation distance between two consecutive removed segments within the digital sound file; and

a portion of an encryption key for decrypting the encrypted first data file.

66. (Currently amended) The ~~computer program product~~article of claim 65, wherein the first and second data files each include one or more segments, and combining the decrypted first data file and the second data files to form the digital sound file comprises:

the computing device using the data supplement to position the segments from the first and second data files into the digital sound file.

67. (Currently amended) The ~~computer program product~~article of claim 64, wherein decrypting the encrypted portion(s) of the first data file includes the computing device using a key, at least one parameter of the key determined from information in the second data file.

68. (Currently amended) The ~~computer program product~~article of claim 64 further comprising instructions for storing the selected and the unselected one of the first and second data files in persistent and non-persistent storage respectively.